



CP-155 自動鎖蓋機(側旋式)

Automatic Capping Machine (Side-rotary-wheel type)

適用範圍：

- 採「側旋式」鎖蓋，適用各式瓶蓋：噴槍蓋、泵浦蓋、上掀蓋、圓帽蓋、防盜蓋、壓頭蓋、安全環蓋...等不同蓋型。
- 方瓶、圓瓶、橢圓瓶及各式特殊瓶型皆適合。
- 適合每日產能較大，且產品多樣化的生產需求。

特色介紹：

- 採用伺服馬達，可輕鬆設定鎖蓋扭力，不易損傷瓶蓋表面。
- 日本三菱PLC，搭配7"吋彩色觸控螢幕，操作簡單易上手。
- 採用德國大廠SICK感測器(電眼)，品質穩定、感應準確。
- 記憶50組配方，可生產多種產品，不需重覆設定。
- 大多數更換模具「免工具」拆卸或調整，換線超快速。
- 鎖蓋滾輪採用特殊彈性體，材質耐磨有保證，免時常更換。
- 依瓶蓋造型不同，可選購自動下蓋裝置，提升產能。

機台規格：

機台尺寸	1500(長) x 750(寬) x 1650(高) mm
機台產能	約 20 瓶 / 每分鐘
適用瓶子高度	100 ~ 280 mm (超出此範圍可客製)
進/收瓶轉盤(選配)	多種轉盤直徑 / 僅適用於圓瓶

Field of Application :

- Side-wrap capping by 4 side-rotary wheels, suitable for various specialty caps, such as Spray / Pump / Flip-up / Child Resistant / Tamper Resistant Caps, etc.
- Suitable for Flat / Square / Oval Bottles and other special shape of bottles.
- Most suitable for larger production with many different products.

Features :

- Servomotor of capping system offers easy adjustments for capping torque and speed to protect caps surface well without scratches.
- Japan Mitsubishi PLC and 7" color touch screen (HMI) for convenient operation.
- SICK sensor (a famous German brand) provides precise and stable performance.
- 50 sets of memory storage are perfect for various products.
- Most changeover or adjustments are simple without using any tools.
- Side-rotary wheels are made by special material for good abrasion resistance.
- 2nd optional automatic cap-feeding device is available for different caps.

Specifications:

Machine Dimension	1500(L) x 750(W) x 1650(H) mm
Production Capacity	About 20 PCS / per minute
Suitable bottle height	100 ~ 280 mm (customized height available)
Bottle Turntable (optional)	Feeding or collecting round bottles

