

# DVR4K-4XTCDP

# DVR4K-8XTCDP

# DVR4K-16XTCDP

4K 8MP ULTRA HD HYBRID 4CH DVR, H.265, AHD,TVI, CVI, IP, ANALOG

4K 8MP ULTRA HD HYBRID 8CH DVR, H.265, AHD,TVI, CVI, IP, ANALOG

4K 8MP ULTRA HD HYBRID 16CH DVR, H.265, AHD,TVI, CVI, IP, ANALOG

## FEATURES


- Coaxial Remote Control On Camera OSD And Lens Zoom In/Out
- Photo Capture on DVR During Live View And Playback
- Capture Schedule: Manual/Normal/Motion/Alarm
- Hybrid Signals: AHD, TVI, CVI, IP Cam, Analog, or Mixed
- Playback Smart Search: Select an Area and Jump Directly to When Motion was Detected in That Area
- PC Software for Windows and Mac OS up to 128CH Live View
- Intelligent Analysis: PID (Perimeter Intrusion Detect), LCD(Line Crossing Detect), SOD(Stationary Object Detect), and More



## SPECIFICATION

| MODEL                 | DVR4K-4XTCDP  | DVR4K-8XTCDP  | DVR4K-16XTCDP                                  |
|-----------------------|---|---|--|
| Description           | H.265/H.264 Hybrid 4K 8MP 4CH DVR   | H.265/H.264 Hybrid 4K 8MP 8CH DVR   | H.265/H.264 Hybrid 4K 8MP 16CH DVR             |
| Video Input           | 4ch input(BNC)+2CH(IP) or 6CH IP  | 8ch input(BNC)+4CH(IP) or 12CH IP   | 16ch input(BNC)+8CH(IP) or 24CH IP             |
| Video Output          | 2ch Output (VGA*1, HD*1)  |   |  |
| Screen Split          | 1/ 4/ 8 (Live) ; 1/ 4 (Playback)  | 1/ 4/ 8/ 12 (Live) ; 1/ 4/ 8 (Playback)   | 1/ 4/ 8/ 16/ 32 (Live); 1/ 4/ 8/ 16 (Playback) |
| Display               | Coax HD: 8MP(15fps) ; 5MP(20fps) ; 4MP/3MP/1080P/720P/960H(real-time) IP Cam:4MP/3MP/1080P/720P   |   |  |
| IP Record Bandwidth   | 16~48Mbps(remove one Coax HD = add 8Mbps)   | 32~96Mbps(remove one Coax HD = add 8Mbps)   | 64Mbps   |
| Playback Resolution   | Coax HD, Analog: fps of each channel<br>4CH DVR: 8MP(6fps) , 5MP(8fps) , 4MP(10fps) , 3MP(12fps) , 1080P/720P/960H(Real-Time)<br>8CH DVR: 8MP(7fps) , 5MP(10fps) , 4MP(15fps) , 3MP(17fps) , 1080P/720P/960H(Real-Time)<br>16CH DVR: 8MP(7fps) , 5MP(10fps) , 4MP(15fps) , 3MP(17fps) , 1080P/720P/960H(Real-Time)<br>IP Cam:<br>4MP/3MP/1080P/720P up to 30fps(NTSC) / 25fps(PAL) , each channel |   |  |
| Alarm Input/ Output   | -   | 8ch sensor input &1ch alarm out   | 16ch sensor input &1ch alarm out               |
| Alarm Type            | Motion Detection/ Video Loss/ Disk Full / Disk Error/ Intelligent   | Sensor Trigger/ Motion Detection / Video Loss/ Disk Full/ Disk Error/ Intelligent |  |
| Storage               | SATA HDD, Up to 6TB ( 8TB*1 HDD)  | SATA HDD, Up to 16TB ( 8TB*2 HDD)   | SATA HDD, Up to 16TB ( 8TB*2 HDD)              |
| Record Mode           | Continue/ Motion Detect/ Schedule/ Manual   | Continue/ Motion Detect/ Schedule/ Manual/ Alarm/ PIR                             |  |
| Intelligent Analysis  | Perimeter Intrusion Detect, Line Crossing Detect, Stationary Object Detect, Pedestrian Detect, Cross Counting   |   |  |
| Back-up               | USB Flash Drive, USB HDD, Network   |   |  |
| Audio                 | 4ch Input/ 1ch Output (RCA)   | 8ch Input/ 1ch Output (RCA)   | 16ch Input/ 1ch Output (RCA)                   |
| HDMIG/VGA             | 800*600,1024*768, 1280*1024,1440*900, 1920*1080 (4CH DVR)   |   |  |
| HDMIG/VGA             | 800*600,1024*768, 1280*1024,1440*900, 1920*1080, 1680*1050, 1600*1200, 1920*1200, 2560*1440, 3840*2160 (8CH &16CH DVR)  |   |  |
| Network Protocol      | TCP/IP, DHCP, DDNS, PPPoE   |   |  |
| Network Functionality | Support IE, Google Chrome and Safari Real-Time Network Monitoring, Network DVR Parameter Setting  |   |  |
| PTZ Control           | Coax, RS-485 Interface (Pelco-D, Pelco-P)   |   |  |
| Size                  | 300mm X 227mm X 47mm  |   | 378mm X 340mm X 47mm                           |
| IR Remote Controller  | Yes   |   |  |
| Weight                | 0.99 kg   | 1.03 kg   | 2.5 kg   |
| Power Supply          | ADAPTER (12V DC 2A)   |   | ADAPTER (12V DC 5A)                            |

## DIMENSION



Unit : mm