


Campro

CB-RS400A

4.0MP HD Hybrid 30M IR Camera



* OSD / UTC Support



CB-RS400A

Pick Up Element	1/2.9" 6.82MP SONY IMX326
Picture Element	2688(H) x 1520(V)
Resolution	4MP: 2688 x 1520@25fps
Lens Type	3.6 / 6.0 / 8.0mm 5.0 Mega Pixel ICR Lens
Optical Filter	With IR-Cut Filter removable (ICR) Design
Sync. System	Internal
Scanning System	2 : 1 Interlace
Min. Illumination	0.01 Lux color / F1.2 / 0 Lux IR On
S/N Ratio	More Than 55dB (AGC OFF)
WDR	D-WDR On / Off
Day/Night Mode	Ext / Auto / Color / B&W
Electronic Shutter	Auto / Manual: 1/50(1/60) – 1/50,000sec.
White Balance	ATW / AWC-SET / Indoor / Outdoor / MWB
Gain Control	Adjustable Auto Gain Control
Backlight Compensation	N/A
DNR	2D DNR
Sharpness Adjustment	OFF / Auto
Brightness Adjustment	Adjustable Brightness
Transmission Distance	RG59 Coaxial Cable -300M / RG6U Coaxial Cable -500M
Twisted Cable Transmission Distance	Max. 300M
Video Output	AHD / CVI / TVI (1520P) & Analog Composite Video, Switchable
Operating Temp.	-10°C ~ 50°C / RH 85% or Less
Power Supply	DC 12V ± 10%
Weatherproof	IP66
Construction Coaxial Cable	Aluminum

IR Distance / IR Led	30M / 6 x 20 MIL Array IR Led
IR Led Activation	10 Lux
Dimension	200(L) x 60(W) x 60(H)mm
Weight	500g
Certification	CE / FCC / RoHS