

# GOLDEN WARRIOR



Engine model	125CC
Engine type	Single Cylinder,4-stroke,air-cooled
Cylinder displacement(ml)	124.8
Broke*stroke	54*54mm
Ignition method	CDI
Maximum Power Kw/(r/min)	8.0/9500r/min
Maximum Torque N·m/(r/min)	9.5/8500r/min
Minimum fuel consumption(g/kw·h)	≤367g/kw·h
Compression ratio	11.5:1
Start type	Electronic/Kick
Transmission	4 gears
Brake type(F/R)	drum
Clutch type	manual
LxWxH(mm) & N.W.(kg)	1780x750x920mm / 80kgs
Min.Ground Clearance(mm)	1400mm
Max.speed(km/h)	85
Wheel(F/R)	2.5-17/2.75-17
Color	Light blue/lightgreen/customized
Fuel tank Maximum capacity(L)	4
Max loading	150kgs



Engine model	110CC
Engine type	Single Cylinder,4-stroke,air-cooled
Cylinder displacement(ml)	109.7
Broke*stroke	53.4x48.8mm
Ignition method	CDI
Maximum Power Kw/(r/min)	5.9/7500/min
Maximum Torque N·m/(r/min)	8.2/6000r/min
Minimum fuel consumption(g/kw·h)	≤367g/kw·h
Compression ratio	9.6:1
Start type	Electronic/Kick
Transmission	4 gears
Brake type(F/R)	drum
Clutch type	automaticl
LxWxH(mm) & N.W.(kg)	1780x750x1050mm 80kgs
Min.Ground Clearance(mm)	1400mm
Max.speed(km/h)	85
Wheel(F/R)	2.25-17/2.5-17
Color	Apple green/customized
Fuel tank Maximum capacity(L)	4
Max loading	150kgs

Optional : riser handle bar



# TL-GR3



Engine model	50CC
Engine type	Single Cylinder,4-stroke,air-cooled
Cylinder displacement(ml)	49.46
Broke*stroke	39*41.4mm
Ignition method	CDI
Maximum Power Kw/(r/min)	2.4/8000r/min
Maximum Torque N·m/(r/min)	3.0/7500r/min
Minimum fuel consumption(g/kw·h)	≤450g/kw·h
Compression ratio	7.3:1
Start type	Electronic/Kick
Transmission	4 gears
Brake type(F/R)	automatic
Clutch type	manual
LxWxH(mm) & N.W.(kg)	1780x750x1030mm / 90kgs
Min.Ground Clearance(mm)	1400mm
Max.speed(km/h)	50
Wheel(F/R)	3.0-13/3.0-13
Color	Blue/Red
Fuel tank Maximum capacity(L)	4
Max loading	150kgs



Engine model	50CC
Engine type	Single Cylinder,4-stroke,air-cooled
Cylinder displacement(ml)	109.7
Broke*stroke	53.4×48.8mm
Ignition method	CDI
Maximum Power Kw/(r/min)	5.9/7500/min
Maximum Torque N·m/(r/min)	8.2/6000r/min
Minimum fuel consumption(g/kw·h)	≤367g/kw·h
Compression ratio	9.6:1
Start type	Electronic/Kick
Transmission	4 gears
Brake type(F/R)	disc/drum
Clutch type	automatic
L×W×H(mm) & N.W.(kg)	/ 90kgs
Min.Ground Clearance(mm)	1400mm
Max.speed(km/h)	85
Wheel(F/R)	3.0-13/3.0-13
Color	Light Blue/light green/customized
Fuel tank Maximum capacity(L)	4
Max loading	150kgs