

NVR4K-41-POE

NVR4K-82-POE

NVR4K-161-POE

4CH H.265 4K NVR, 4CH POE PORTS, e-SATA, USB 3.0

8CH H.265 4K NVR, 8CH POE PORTS, e-SATA, USB 3.0

16CH H.265 4K NVR, 16CH POE PORTS, e-SATA, USB 3.0

FEATURES

- OnVif 2.6 (H.264)
- Plug & View UHD 4K/ 8MP Resolution
- HDD S.M.A.R.T.: Self-Monitoring Analysis & Reporting Technology
- Redundancy Disk (8CH & 16CH)
- e-SATA Record & Backup
- Disk Group Management (8CH & 16CH)
- Dropbox Cloud Storage
- Voice Intercom between NVR and IE/ CMS
- Selectable Zoom Area During Live View And Playback
- Simultaneous HD Live View And Playback on The Same Screen
- Sub-Period Playback: Playback the same channel in different times w/ multiple-windows.
- CMS for Windows and Mac OS with 128CH Live View
- App for iOS and Android OS: 16CH/ 36CH Live View and 4CH Remote Playback



SPECIFICATION

MODEL	NVR4K-41-POE	NVR4K-82-POE	NVR4K-161-POE
Video Input	4 x PoE Ports	8 x PoE Ports	16 x PoE Ports
Video Output	2CH Output (HD*1, VGA*1)		
Display Split	1/ 4	1/ 4/ 6/ 8/ 9	1/ 4/ 6/ 8/ 9/ 10/ 13/ 14/ 16
Display Resolution	3840x2160,2560x1440,1900x1200,1600x1200,1180x1050,1920x1080,1280x1024,1440x900,1280x720,1024x768		
Live/ Playback Resolution	2CH 4K (3840 X 2160), Real-Time 4CH 4.0MP (2592 X 1520), Real-Time	4CH 4K (3840 X 2160), Real-Time 8CH 4.0MP (2592 X 1520), Real Time	4CH 4K (3840 X 2160), Real-Time 8CH 4.0MP (2592 X 1520), Real Time 16CH 2.0MP (1920 X 1080), Real Time
Record Resolution	8.0MP (4K), 4.0MP, 3.0MP, 2.0MP (1080P), 1.3MP (960P), 1.0MP (720P)		
Record Bandwidth	Max. 50Mbps	Max. 100Mbps	Max. 320Mbps
Record Mode	Continuous/ Manual/ Schedule/ Motion Detect/ Sensor/ Alarm		
Intercom	Line In/ Audio Out; RCA x 2		
Ethernet	RJ-45 Port (1000M)		
Alarm Input/ Output	4CH In / 1CH Out	8CH In / 1CH Out	16CH In / 1CH Out
Audio Input/ Output	4CH IPC In/ 1CH Out (RCA)	8CH IPC In/ 1CH Out (RCA)	16CH IPC In/ 1CH Out (RCA)
Storage	8TB (8TB*1 SATA HDD)	16TB (8TB*2 SATA HDD)	
RS485	YES		
e-SATA	YES (for Record & Backup)		
Backup	USB Flash Drive, USB HDD, Network		
Backup Format	.avi/ .mp4/ .265 file		
Remote Access	Browser: IE 11, Google Chrome 42/43/44, Firefox, Safari 6.0 Client Software: Windows and Mac OS with 128CH Live View Mobile: App for iOS and Android Devices		
USB Interface	1 x USB 3.0 for Backup/ Upgrade, 2 x USB 2.0 for Backup/ Mouse		
Size	300mm X 227mm X 53mm	380mm X 340mm X 50mm	
Weight	1.1 kg	2.5 kg	2.9 kg
Power Supply	ADAPTER (48V DC 1.2A)	ADAPTER (48V DC 2A)	AC 110V ~ 240V, 190W
Built-In PoE Switch	48V DC		

DIMENSION

